SMARTS

Visoglide Plus

Smarts' main thermally broken sliding door for large openings, as an inline slider or lift & slide.

Key features

- ✓ Sashes up to 2500mm high and 250kg
- ✓ Inline or lift & slide
- ✓ Slim interlock option
- ✓ Compatible with automatic opening kits
- ✓ Quick-Glaze bead and co-extruded gaskets
- ✓ PAS 24:2022 with BSI Kitemark

Options

- ✓ Double or triple glazing (38mm)
- ✓ Dual colour including Sensations
- ✓ Colour-matched accessories

Specification

U-value	1.4 W/m²K (1.0 centre pane) · 1.1 W/m²K (0.7 centre pane)
Max sash	2500mm high, 250kg; no max width within those limits
Glazing	38mm double or triple
Outer frame sightline	117mm
Interlock	83mm
Weather	Air Class 3 (600Pa) · Water 7a (300Pa) · Wind AE 2400Pa
Security	PAS 24:2022; Kitemark KM 530838; BS 6375-1

Configurations

2-pane | 3-pane | 4-pane | Inline | Lift & slide



Talk to us about Visoglide Plus

Survey, design advice and a written quotation.
18 Winton Road, Farnborough, Orpington BR6 7AL

01689 851 938
info@visaglaze.co.uk
www.visaglaze.co.uk

Information is taken from the manufacturer's published data and is provided as a guide. Sizes and performance depend on the final configuration, glass and hardware. Please ask us to confirm details for your project.